

SPECIFICATION FOR LCM+RTP Module

MODULE No:	KD070HDFIA030-RT
CUSTOMER:	

STARTEK	INITIAL	DATE
PREPARED BY		
CHECKED BY		
APPROVED BY		

CUSTOMER	INITIAL	DATE
APPROVED BY		

Part. No	KD070HDFIA030-RT	REV	V1.0	Page 1 of 31
常备库存 Stock For Sale	长期供货 Long Time supply	支持小量 NO MOQ	品种齐全 In Full Range	

[illegible]

Part. No	KD070HDFIA030-RT	REV	V1.0	Page 2 of 31
常 备 库 存 Stock For Sale	长 期 供 货 Long Time supply	支持小量 NO MOQ	品 种 齐 全 In Full Range	

Contents

1. Block Diagram	5
2. Outline dimension	6
3. Input terminal Pin Assignment	7
4. LCD Optical Characteristics	9
4.1 Optical specification	9
5. Electrical Characteristics	12
5.1 Absolute Maximum Rating	12
5.2 DC Electrical Characteristics	12
5.3 LED Backlight Characteristics	13
6. MIPI AC Characteristic	15
6.1 LP Transmitter AC Specification	15
6.2 Turnaround Procedure	16
6.3 High speed transmission	17
6.4 High Speed Clock Transmission	18
6.5 High Speed Data Transmission in Bursts	19
7. TP Feature	20
7.1 Conditions of use and storage	20
7.2 Electrical property	20
7.3 Mechanical property	21
7.4 Optical propertys	21
8. LCD Module Out-Going Quality Level	22
8.1 VISUAL & FUNCTION INSPECTION STANDARD	22
8.1.1 Inspection conditions	22
8.1.2 Definition	22
8.1.3 Sampling Plan	23
8.1.4 Criteria (Visual)	24
9. Reliability Test Result	29
10. Cautions and Handling Precautions	30
10.1 Handling and Operating the Module	30
10.2 Storage and Transportation	30
11. Packing	31

Part. No	KD070HDFIA030-RT	REV	V1.0	Page 3 of 31
常 备 库 存 Stock For Sale	长 期 供 货 Long Time supply	支持小量 NO MOQ	品 种 齐 全 In Full Range	

* Description

This is a color active matrix TFT (Thin Film Transistor) LCD (liquid crystal display) that uses amorphous silicon TFT as a switching device. This module is composed of a Transmissive type TFT-LCD Panel, driver circuit, 4 wires resistance touch screen, back-light unit. The resolution of a 7.0 " TFT-LCD contains 1024x600 pixels, and can display up to 16.7M colors.

* Features

General Information Items	Specification	Unit	Note
	Main Panel		
Display area(AA)	154.21(H)*85.92 (V) (7.0inch)	mm	
Driver element	TFT active matrix	-	
Display colors	16.7M	colors	
Number of pixels	1024(RGB)*600	dots	
Pixel arrangement	RGB vertical stripe	-	
Pixel pitch	0.1506(H)*0.1432(V)	mm	
Viewing angle	Free	o'clock	
Controller IC	EK73217BCGA+EK79007AD2	-	
LCM Interface	4Lane MIPI	-	
Display mode	Transmissive /Normally Black	-	
Operating temperature	-20~+70	°C	
Storage temperature	-30~+80	°C	


* Mechanical Information

Item		Min.	Typ.	Max.	Unit	Note
Module size	Horizontal(H)	-	165	-	mm	
	Vertical(V)	-	100	-	mm	
	Depth(D)	-	7.3	-	mm	
Weight		-	--	-	g	


Part. No	KD070HDFIA030-RT	REV	V1.0	Page 4 of 31
常备库存 Stock For Sale	长期供货 Long Time supply	支持小量 NO MOQ	品种齐全 In Full Range	



1. Block Diagram



2. Outline dimension



Part. No	KD070HDFIA030-RT	REV	V1.0	Page 6 of 31
常备库存 Stock For Sale	长期供货 Long Time supply	支持小量 NO MOQ	品种齐全 In Full Range	

3. Input terminal Pin Assignment

NO.	SYMBOL	DISCRIPTION	I/O
1	LEDK	LED Cathode	P
2	LEDK	LED Cathode	P
3	NC		
4	LED A	LED Anode	P
5	LED A	LED Anode	P
6	NC		
7	VDD_1.8V	Power supply for digital circuits	P
8	NC		
9	VDD_3.3V	Power supply for DC/DC convert circuit	P
10	UD	Vertical shift direction (gate output) selection(NOTE1)	I
11	LR	Horizontal shift direction (source output) selection(NOTE1)	I
12	RESET	Global reset pin. Active low to enter reset state.	I
13	STBYB	Standby mode, Normally pulled high STBYB = "1", normal operation STBYB = "0", timing controller, source driver will turn off, all o utput are High-Z.	I
14	GND	Ground	P
15	D0N	MIPI DSI differential data pair (Data lane 0)	I/O
16	D0P		
17	GND	Ground	P
18	D1N	MIPI DSI differential data pair (Data lane 1)	I/O
19	D1P		
20	GND	Ground	P
21	CLKN	MIPI DSI differential clock pair .	I
22	CLKP		
23	GND	Ground	P
24	D2N	MIPI DSI differential data pair (Data lane 2)	I/O
25	D2P		
26	GND	Ground	P
27	D3N	MIPI DSI differential data pair (Data lane 3)	I/O


28	D3P	MIPI DSI differential data pair (Data lane 3)	
29	GND	Ground	P
30	GND	Ground	P

Note1: When L/R="0", set right to left scan direction.

When L/R="1", set left to right scan direction.

When U/D="0", set top to bottom scan direction.

When U/D="1", set bottom to top scan direction.



4. LCD Optical Characteristics

4.1 Optical specification

Item		Symbol	Condition	Min.	Typ.	Max.	Unit.	Note
Contrast Ratio		CR	$\Theta=0$ Normal viewing angle	600	800	--		(1)(2)
Response time	Rising	T_{R+T_F}		--	25	40	msec	(1)(3)
	Falling							
Uniformity		S(%)		--	50	--	%	
Color Filter Chromaticity	White	W_X	$\Theta = 0^\circ$	0.2584	0.2984	0.3384		(1)(4)
		W_Y		0.3000	0.3400	0.3800		
	Red	R_X		0.5731	0.5931	0.6131		
		R_Y		0.3352	0.3552	0.3752		
	Green	G_X		0.2909	0.3109	0.2909		
		G_Y		0.5344	0.5544	0.5744		
	Blue	B_X		0.1334	0.1534	0.1734		
		B_Y		0.0872	0.1072	0.1272		
Viewing angle	Hor.	Θ_L	CR>10	--	85	--		(1)(4)
		Θ_R		--	85	--		
	Ver.	Θ_U		--	85	--		
		Θ_D		--	85	--		
Option View Direction		FREE						


Measuring Condition
Measuring surrounding : dark room
Ambient temperature : 25±2°C
15min. warm-up time.

Measuring Equipment
FPM520 of Westar Display technologies, INC., which utilized SR-3 for Chromaticity and BM-5A for other optical characteristics.

Part. No	KD070HDFIA030-RT	REV	V1.0	Page 9 of 31
常备库存 Stock For Sale	长期供货 Long Time supply	支持小量 NO MOQ	品种齐全 In Full Range	




Note (1): Definition of Viewing Angle :



Note (2): Definition of Contrast Ratio(CR) :measured at the center point of panel

$$CR = \frac{\text{Luminance with all pixels white}}{\text{Luminance with all pixels black}}$$


Note (3): Response Time



Part. No	KD070HDFIA030-RT	REV	V1.0	Page 10 of 31
常备库存 Stock For Sale	长期供货 Long Time supply	支持小量 NO MOQ	品种齐全 In Full Range	



Note (4): Definition of optical measurement setup



Part. No	KD070HDFIA030-RT	REV	V1.0	Page 11 of 31
常备库存 Stock For Sale	长期供货 Long Time supply	支持小量 NO MOQ	品种齐全 In Full Range	

5. Electrical Characteristics

5.1 Absolute Maximum Rating

Characteristics	Symbol	Min.	Max.	Unit	Note
Power supply for digital circuits	VDD_1.8V	-0.3	2.0	V	Note1
Power supply for DC/DC convert circuit	VDD_3.3V	-0.3	6.0	V	Note1
Operating temperature	T _{OP}	-20	+70	°C	
Storage temperature	T _{ST}	-30	+80	°C	

NOTE1: If the absolute maximum rating of even is one of the above parameters is exceeded even momentarily, the quality of the product may be degraded. Absolute maximum ratings, therefore, specify the values exceeding which the product may be physically damaged. Be sure to use the product within the range of the absolute maximum ratings.

5.2 DC Electrical Characteristics

Characteristics	Symbol	Min.	Typ.	Max.	Unit	Note
Power supply for digital circuits	VDD_1.8V	1.71	1.8	1.89	V	
Power supply for DC/DC convert circuit	VDD_3.3V	2.7	3.3	5.8	V	
Normal mode Current	IDD_1.8V	--	0.05	--	mA	
Normal mode Current	IDD_3.3V	--	140	--	mA	
Low Level input voltage	V _{IH}	0.7*VDD_1.8V	--	VDD_1.8V	V	
	V _{IL}	0	--	0.3*VDD_1.8V	V	

Part. No	KD070HDFIA030-RT	REV	V1.0	Page 12 of 31
常备库存 Stock For Sale	长期供货 Long Time supply	支持小量 NO MOQ	品种齐全 In Full Range	

High Level output voltage	V_{OH}	VDD_1.8 V-0.4	--	VDD_1.8 V	V	
	V_{OL}	0	--	0.4	V	

5.3 LED Backlight Characteristics

The back-light system is edge-lighting type with 27 chips LED


Item	Symbol	Min.	Typ.	Max.	Unit	Note
Forward Current	I_F	180	270	--	mA	
Forward Voltage	V_F	--	9.6	--	V	
LCM Luminance ($I_F = 180\text{mA}$)	LV	310	360	--	cd/m ²	Note3
LCM Luminance ($I_F = 270\text{mA}$)	LV	430	480	--	cd/m ²	Note3
LED life time	Hr	--	50000	--	Hour	Note1,2
Uniformity	Avg	80	--	--	%	Note3

Note1: LED life time (Hr) can be defined as the time in which it continues to operate under the condition:

$T_a = 25 \pm 3^\circ\text{C}$, typical IL value indicated in the above table until the brightness becomes less than 50%.

Note 2: The "LED life time" is defined as the module brightness decrease to 50% original brightness at


$T_a = 25^\circ\text{C}$ and $I_L = 270\text{mA}$. The LED lifetime could be decreased if operating I_L is larger than 270mA. The constant current driving method is suggested.



B/L Circuit

Part. No	KD070HDFIA030-RT	REV	V1.0	Page 13 of 31
常备库存 Stock For Sale	长期供货 Long Time supply	支持小量 NO MOQ	品种齐全 In Full Range	

Note (3) Luminance Uniformity of these 9 points is defined as below:




$$\text{Uniformity} = \frac{\text{minimum luminance in 9 points (1-9)}}{\text{maximum luminance in 9 points (1-9)}}$$

$$\text{Luminance} = \frac{\text{Total Luminance of 9 points}}{9}$$

6. MIPI AC Characteristic

6.1 LP Transmitter AC Specification


Parameter	Symbol	Min	Typ	Max	Units	Notes
15%~85% rising time and falling time	T_{RLP} / T_{FLP}	-	-	25	ns	-
30%~85% rising time and falling time	T_{REOT}	-	-	35	ns	-
Pulse width of LP exclusive-OR clock	$T_{LP-PULSE-TX}$	40	-	-	ns	-
		20	-	-	ns	-
Period of the LP EXOR clock	$T_{LP-PER-TX}$	90	-	-	mV/ns	-
Slew Rate @CLOAD =0pF	$\delta V / \delta t_{SR}$	30	-	500	mV/ns	-
Slew Rate @CLOAD =5pF		30	-	200	mV/ns	-
Slew Rate @CLOAD =20pF		30	-	150	mV/ns	-
Slew Rate @CLOAD =70pF		30	-	100	mV/ns	-
Load Capacitance	T_{RLP}	-	-	70	pF	-



6.2 Turnaround Procedure


Turnaround Procedure Operation Timing Parameters

Parameter	Symbol	Min	Typ	Max	Units
Length of any Low-Power state period: Master side	T _{LPX}	50	-	75	ns
Length of any Low-Power state period: Slave side	T _{LPX}	50	55.56	58.34	ns
Ratio of T _{LPX} (Master)/ T _{LPX} (Slave) between Master and Slave side	Ratio T _{LPX}	2/3	-	3/2	
Time-out before new TX side start driving	T _{TA-Sure}	T _{LPX}	-	2T _{LPX}	ns
Time to drive LP-00 by new TX	T _{TA-GET}	-	5T _{LPX}	-	ns
Time to drive LP-00 after Turnaround Request	T _{TA-GO}	-	4T _{LPX}	-	ns




6.3 High speed transmission

Parameter	Symbol	Min	Typ	Max	Units
UI instantaneous	UI _{INST}	2	-	12.5	ns
Data to Clock Skew(measured at transmitter)	T _{SKEW(TX)}	-0.15	-	0.15	UI _{INST}
Data to Clock Setup time(measured at receiver)	T _{SETUP(RX)}	0.15	-	-	UI _{INST}
Data to Clock Hold time(measured at receiver)	T _{HOLD(RX)}	0.15	-	-	UI _{INST}
20%~80% rise time and fall time	T _R , T _F	150	-	-	ps
		-	-	0.3	UI _{INST}




6.4 High Speed Clock Transmission

Parameter	Symbol	Min	Typ	Max	Units
Time that the transmitter shall continue sending HS clock after the last associated Data Lane has transitioned to LP mode	TCLK-POST	60+52UI	-	-	ns
Detection time that the clock has stopped toggling	TCLK-MISS	-	-	60	ns
Time to drive LP-00 to prepare for HS clock transmission	TCLK-PREPARE	38	-	95	ns
Minimum lead HS-0 drive period before starting clock	TCLK-PREPARE + TCLK-ZERO	300	-	-	ns
Time to enable Clock Lane receiver line termination measured from when Dn cross V_{ILMAX}	THS-TERM-EN	-	-	38	ns
Minimum time that the HS clock must be prior to any associated data lane beginning the transmission from LP to HS mode	TCLK-PRE	8	-	-	UI
Time to drive HS differential state after last payload clock bit of a HS transmission burst	TCLK-TRAIL	60	-	-	ns



6.5 High Speed Data Transmission in Bursts





7. TP Feature

7.1 Conditions of use and storage

Item	Value(condition)	Note
Temperature range upon operation	Humidity: 20%~90% non dew, condensation -20℃~70℃	In a simple substance
Temperature range upon storage	Humidity: 20%~90% non dew, condensation -30℃~80℃	In a simple substance

7.2 Electrical property

Item	Value	Note
Maximum voltage	DC5V	
Resistance between terminals	X direction[Film side]:200-600Ω	
	Y direction [Glass side]:300-900Ω	
Insulation resistance	DC 25V 20MΩor above	Connect X + ~X- and Y+ ~Y-, apply 25VDC Between X and Y for perform measurements
Chattering	10 msec or below	
Rating	Voltage is DC 5V	



Part. No	KD070HDFIA030-RT	REV	V1.0	Page 20 of 31
常备库存 Stock For Sale	长期供货 Long Time supply	支持小量 NO MOQ	品种齐全 In Full Range	

7.3 Mechanical property

Item	Performance		Note
Input method	Used of an exclusive pen or finger		
Load upon operation	Exclusive pen	60-100g or below	Operation and measurement with a pen must be carried out under the following tip condition s: Stylus pen material : POM(ployacetal) . Tip : Diameter 3.0mm, SR 0.8 mm
	Finger	60-100g or below	Operations and measurement methods simulate d for a finger must be carried out under the fo llowing tip conditions. Material :Silicon rubber (Hardness : 30°Hs) Tip : Diameter 12.0 mm, SR 12.5mm
Surface hardness	Pencil hardness : 3H or above		It complies with the way of test method JIS K5400.

7.4 Optical property

Item	Performance	Note
Total light transmittance	80% or above	JIS K7105
Haze	5% or below	JIS K7136
Film specification	Polished type with hard coated surface	


8. LCD Module Out-Going Quality Level

8.1 VISUAL & FUNCTION INSPECTION STANDARD


8.1.1 Inspection conditions

Inspection performed under the following conditions is recommended.

- Temperature : 25±5℃
- Humidity : 65%±10%RH
- Viewing Angle : Normal viewing Angle.
- Illumination: Single fluorescent lamp (300 to 700Lux)
- Viewing distance:30-50cm



8.1.2 Definition



- Zone A : Effective Viewing Area(Character or Digit can be seen)
- Zone B : Viewing Area except Zone A
- Zone C : Outside (Zone A+Zone B) which can not be seen after assembly by customer .)
- Zone D : IC Bonding Area

Note:As a general rule ,visual defects in Zone C can be ignored when it doesn't effect product function or appearance after assembly by customer

Part. No	KD070HDFIA030-RT	REV	V1.0	Page 22 of 31
常备库存 Stock For Sale	长期供货 Long Time supply	支持小量 NO MOQ	品种齐全 In Full Range	

8.1.3 Sampling Plan

According to GB/T 2828.1-2003 ; , normal inspection, Class II




AQL:

Major defect	Minor defect
0.65	1.5

LCD: Liquid Crystal Display , TP: Touch Panel , LCM: Liquid Crystal Module


No	Items to be inspected	Criteria	Classification of defects
1	Functional defects	1) No display, Open or miss line 2) Display abnormally, Short 3) Backlight no lighting, abnormal lighting. 4) TP no function	Major
2	Missing	Missing component	
3	Outline dimension	Overall outline dimension beyond the drawing is not allowed	
4	Color tone	Color unevenness, refer to limited sample	Minor
5	Spot Line defect	Light dot, Dim spot,Polarizer Bubble ; Polarizer accidented spot.	
6	Soldering appearance	Good soldering , Peeling off is not allowed.	
7	LCD/Polarizer/TP	Black/White spot/line, scratch, crack, etc.	

8.1.4 Criteria (Visual)

Number	Items	Criteria(mm)						
1.0 LCD Crack/Broken NOTE: X: Length Y: Width Z: Height L: Length of ITO, T: Height of LCD	(1) The edge of LCD broken	 <table><tr><td>X</td><td>Y</td><td>Z</td></tr><tr><td>≤3.0mm</td><td><Inner border line of the seal</td><td>≤T</td></tr></table>	X	Y	Z	≤3.0mm	<Inner border line of the seal	≤T
	X	Y	Z					
	≤3.0mm	<Inner border line of the seal	≤T					
(2)LCD corner broken	 <table><tr><td>X</td><td>Y</td><td>Z</td></tr><tr><td>≤3.0mm</td><td>≤L</td><td>≤T</td></tr></table>	X	Y	Z	≤3.0mm	≤L	≤T	
X	Y	Z						
≤3.0mm	≤L	≤T						
(3) LCD crack	 Crack Not allowed							

2.0

Spot defect



$\Phi=(X+Y)/2$

① light dot (LCD/TP/Polarizer black/white spot , light dot, pinhole, dent, stain)

Zone Size (mm)	Acceptable Qty		
	A	B	C
$\Phi\leq0.10$	Ignore		
$0.10<\Phi\leq0.25$	4(distance $\geq 10\text{mm}$)		
$0.25<\Phi\leq0.35$	3		
$\Phi>0.4$	0		

②Dim spot (LCD/TP/Polarizer dim dot, light leakage、 dark spot)

Zone Size (mm)	Acceptable Qty		
	A	B	C
$\Phi\leq0.1$	Ignore		
$0.10<\Phi\leq0.25$	4(distance $\geq 10\text{mm}$)		
$0.25<\Phi\leq0.35$	3		
$\Phi>0.4$	0		

③ Polarizer accidented spot

Zone Size (mm)	Acceptable Qty		
	A	B	C
$\Phi\leq0.2$	Ignore		
$0.3<\Phi\leq0.5$	3(distance $\geq 10\text{mm}$)		
$\Phi>0.5$	1		

④Pixel bad points (light dot, Dim dot, color dot)


Zone Size (mm)	Acceptable Qty		
	A	B	C
$\Phi\leq0.15$	Ignore		
$0.2<\Phi\leq0.3$	2(distance $\geq 10\text{mm}$)		
$\Phi>0.4$	1		

⑤ Polarizer Bubble

Zone Size (mm)	Acceptable Qty		
	A	B	C
$\Phi\leq0.2$	Ignore		
$0.3<\Phi\leq0.4$	4(distance $\geq 10\text{mm}$)		
$0.4<\Phi\leq0.5$	3		
$\Phi>0.5$	1		

3.0	Line defect (LCD/TP /Polarizer backlight black/white line, scratch, stain)	<table><tr><td rowspan="2">Width(mm)</td><td rowspan="2">Length(m m)</td><td colspan="3">Acceptable Qty</td></tr><tr><td>A</td><td>B</td><td>C</td></tr><tr><td>$\Phi\leq0.05$</td><td>Ignore</td><td colspan="2">Ignore</td><td rowspan="3">Ignore</td></tr><tr><td>$0.05<W\leq0.06$</td><td>$L\leq5.0$</td><td colspan="2">$N\leq3$</td></tr><tr><td>$0.07<W\leq0.08$</td><td>$L\leq4.0$</td><td colspan="2">$N\leq2$</td></tr><tr><td>$0.08<W$</td><td colspan="4">Define as spot defect</td></tr></table>	Width(mm)	Length(m m)	Acceptable Qty			A	B	C	$\Phi\leq0.05$	Ignore	Ignore		Ignore	$0.05<W\leq0.06$	$L\leq5.0$	$N\leq3$		$0.07<W\leq0.08$	$L\leq4.0$	$N\leq2$		$0.08<W$	Define as spot defect			
		Width(mm)			Length(m m)	Acceptable Qty																						
			A	B		C																						
		$\Phi\leq0.05$	Ignore	Ignore		Ignore																						
		$0.05<W\leq0.06$	$L\leq5.0$	$N\leq3$																								
$0.07<W\leq0.08$	$L\leq4.0$	$N\leq2$																										
$0.08<W$	Define as spot defect																											
4.0	Electronic Components SMT	Not allow missing parts, solderless connection, cold solder joint, mis match, The positive and negative polarity opposite																										
5.0	Display color& Brightness	1. Color: Measuring the color coordinates, The measurement standard according to the datasheet or samples. 2. Brightness: Measuring the brightness of White screen, The measurement standard according to the datasheet or Samples.																										
6.0	LCD Mura	By 5% ND filter invisible.																										

7.0	RTP Related	TP film bubble/ accidentec spot	<table><tr><td rowspan="2">Size Φ(mm)</td><td colspan="3">Acceptable Qty</td></tr><tr><td>A</td><td>B</td><td>C</td></tr><tr><td>$\Phi \leq 0.1$</td><td colspan="2">Ignore</td><td rowspan="4">Ignore</td></tr><tr><td>$0.1 < \Phi \leq 0.25$</td><td colspan="2">4 (distance ≥ 10mm)</td></tr><tr><td>$0.25 < \Phi \leq 0.35$</td><td colspan="2">3</td></tr><tr><td>$\Phi > 0.4$</td><td colspan="2">1</td></tr></table>				Size Φ (mm)	Acceptable Qty			A	B	C	$\Phi \leq 0.1$	Ignore		Ignore	$0.1 < \Phi \leq 0.25$	4 (distance ≥ 10 mm)		$0.25 < \Phi \leq 0.35$	3		$\Phi > 0.4$	1							
			Size Φ (mm)	Acceptable Qty																												
				A	B	C																										
			$\Phi \leq 0.1$	Ignore		Ignore																										
			$0.1 < \Phi \leq 0.25$	4 (distance ≥ 10 mm)																												
			$0.25 < \Phi \leq 0.35$	3																												
		$\Phi > 0.4$	1																													
		TP film scratch	<table><tr><td rowspan="2">Width(mm)</td><td rowspan="2">Length(mm)</td><td colspan="3">Acceptable Qty</td></tr><tr><td>A</td><td>B</td><td>C</td></tr><tr><td>$\Phi \leq 0.05$</td><td>Ignore</td><td colspan="2">Ignore</td><td rowspan="3">Ignore</td></tr><tr><td>$0.05 < W \leq 0.06$</td><td>$L \leq 5.0$</td><td colspan="2">$N \leq 3$</td></tr><tr><td>$0.07 < W \leq 0.08$</td><td>$L \leq 4.0$</td><td colspan="2">$N \leq 2$</td></tr><tr><td>$0.08 < W$</td><td colspan="3">Define as spot defect</td></tr></table>				Width(mm)	Length(mm)	Acceptable Qty			A	B	C	$\Phi \leq 0.05$	Ignore	Ignore		Ignore	$0.05 < W \leq 0.06$	$L \leq 5.0$	$N \leq 3$		$0.07 < W \leq 0.08$	$L \leq 4.0$	$N \leq 2$		$0.08 < W$	Define as spot defect			
			Width(mm)	Length(mm)	Acceptable Qty																											
					A	B	C																									
			$\Phi \leq 0.05$	Ignore	Ignore		Ignore																									
			$0.05 < W \leq 0.06$	$L \leq 5.0$	$N \leq 3$																											
$0.07 < W \leq 0.08$	$L \leq 4.0$		$N \leq 2$																													
$0.08 < W$	Define as spot defect																															

		Assembly deflection	beyond the edge of backlight ≤0.2mm								
		Bulge (undulation included)	The ITO film plumped below 0.40mm, it's ok. 								
		Newton Ring	Newton Ring area>1/3 TP area NG Newton Ring area≤1/3 TP area OK								
		TP corner broken X : length Y : width Z : height	<table border="1"><thead><tr><th>X</th><th>Y</th><th>Z</th></tr></thead><tbody><tr><td>X≤3mm</td><td>Y≤3mm</td><td>Z<COVER thickness</td></tr></tbody></table> *Circuitry broken is not allowed.		X	Y	Z	X≤3mm	Y≤3mm	Z<COVER thickness	
X	Y	Z									
X≤3mm	Y≤3mm	Z<COVER thickness									

Criteria (functional items)

Number	Items	Criteria (mm)
1	No display	Not allowed
2	Missing segment	Not allowed
3	Short	Not allowed
4	Backlight no lighting	Not allowed
5	TP no function	Not allowed

9. Reliability Test Result

Item	Condition	Inspection after test
High Temperature Operating	70℃,96H	Inspection after 2~4hours storage at room temperature, the sample shall be free from defects: 1.Air bubble in the LCD; 2.Non-display; 3.Missing segments/line; 4.Glass crack; 5.Current IDD is twice higher than initial value.
Low Temperature Operating	-20℃, 96HR	
High Temperature Storage	80℃, 96HR	
Low Temperature Storage	-30℃, 96HR	
High Temperature & High Operating	+60℃, 90% RH ,96 hours.	
Thermal Shock (Non-operation)	-30℃,30 min ↔ 80℃,30 min, Change time:5min 20CYC.	
ESD test	C=150pF, R=330,5points/panel Air:±8KV, 5times; Contact:±6KV, 5 times; (Environment: 15℃~35℃, 30%~60%).	
Vibration (Non-operation)	Frequency range:10~55Hz, Stroke:1.5mm Sweep:10Hz~55Hz~10Hz 2 hours for each direction of X.Y.Z. (6 hours for total) (Package condition).	
Box Drop Test	1 Corner 3 Edges 6 faces,80cm(MEDIUM BOX)	

Remark:

- 1.The test samples should be applied to only one test item.
- 2.Sample size for each test item is 5~10pcs.
- 3.For Damp Proof Test, Pure water(Resistance > 10MΩ) should be used.
- 4.In case of malfunction defect caused by ESD damage, if it would be recovered to normal state after resetting, it would be judged as a good part.
- 5.Failure Judgment Criterion: Basic Specification, Electrical Characteristic, Mechanical Characteristic, Optical Characteristic.

Part. No	KD070HDFIA030-RT	REV	V1.0	Page 29 of 31
常备库存 Stock For Sale	长期供货 Long Time supply	支持小量 NO MOQ	品种齐全 In Full Range	

10. Cautions and Handling Precautions

10.1 Handling and Operating the Module

- (1) When the module is assembled, it should be attached to the system firmly.
Do not warp or twist the module during assembly work.
- (2) Protect the module from physical shock or any force. In addition to damage, this may cause improper operation or damage to the module and back-light unit.
- (3) Note that polarizer is very fragile and could be easily damaged. Do not press or scratch the surface.
- (4) Do not allow drops of water or chemicals to remain on the display surface.
If you have the droplets for a long time, staining and discoloration may occur.
- (5) If the surface of the polarizer is dirty, clean it using some absorbent cotton or soft cloth.
- (6) The desirable cleaners are water, IPA (Isopropyl Alcohol) or Hexane.
Do not use ketene type materials (ex. Acetone), Ethyl alcohol, Toluene, Ethyl acid or Methyl chloride. It might permanent damage to the polarizer due to chemical reaction.
- (7) If the liquid crystal material leaks from the panel, it should be kept away from the eyes or mouth. In case of contact with hands, legs, or clothes, it must be washed away thoroughly with soap.
- (8) Protect the module from static; it may cause damage to the CMOS ICs.
- (9) Use finger-stalls with soft gloves in order to keep display clean during the incoming inspection and assembly process.
- (10) Do not disassemble the module.
- (11) Protection film for polarizer on the module shall be slowly peeled off just before use so that the electrostatic charge can be minimized.
- (12) Pins of I/F connector shall not be touched directly with bare hands.
- (13) Do not connect, disconnect the module in the "Power ON" condition.
- (14) Power supply should always be turned on/off by the item 6.1 Power On Sequence & 6.2 Power Off Sequence

10.2 Storage and Transportation.

- (1) Do not leave the panel in high temperature, and high humidity for a long time.
It is highly recommended to store the module with temperature from 0 to 35 °C and relative humidity of less than 70%
- (2) Do not store the TFT-LCD module in direct sunlight.
- (3) The module shall be stored in a dark place. When storing the modules for a long time, be sure to adopt effective measures for protecting the modules from strong ultraviolet radiation, sunlight, or fluorescent light.
- (4) It is recommended that the modules should be stored under a condition where no condensation is allowed. Formation of dewdrops may cause an abnormal operation or a failure of the module.
In particular, the greatest possible care should be taken to prevent any module from being operated where condensation has occurred inside.
- (5) This panel has its circuitry FPC on the bottom side and should be handled carefully in order not to be stressed.

Part. No	KD070HDFIA030-RT	REV	V1.0	Page 30 of 31
常备库存 Stock For Sale	长期供货 Long Time supply	支持小量 NO MOQ	品种齐全 In Full Range	

11. Packing

----TBD-----

Part. No	KD070HDFIA030-RT	REV	V1.0	Page 31 of 31
	常 备 库 存 Stock For Sale	长 期 供 货 Long Time supply	支持少量 NO MOQ	品 种 齐 全 In Full Range